

# Tailwater Recovery and On-Farm Storage Reservoir: Water Savings



## Why Save Water Using TWR Systems?

Row-crop irrigation is the primary use of groundwater in the Mississippi Delta region. Currently, withdrawals of water from the aquifer by irrigators is greater than the amount that is recharged (YMD, 2010). **Figure 1** shows the Mississippi Delta region and magnitude of aquifer levels above mean sea level. The groundwater levels range from more groundwater (blue and light blue) to less groundwater (red and orange). Water levels in the aquifer under Sunflower and Leflore Counties are denoted with red because agricultural withdrawal is much greater than recharge. The annual groundwater deficit is estimated to be approximately 150,750 acre-feet (YMD, 2010; Barlow and Clark, 2011).

Several options are available for irrigators to reduce groundwater use. First, they can improve the efficiency of their water use, also known as “at-the-tap conservation” or “more crop per drop.” They can achieve this by using technologies including soil-moisture meters, center-pivot irrigation with drop lines and improved nozzles, or furrow irrigation with pipe planner programs with variable-hole-size selection and surge valves. Second, irrigators can use surface water. This can be done by installing a pump on an existing surface water source or by installing a tailwater recovery (TWR) system.




Figure 1. Ground water levels in the Mississippi Delta. Groundwater data were provided by Yazoo Mississippi Delta Joint Water Management District, Groundwater Level Data (Fall 2016), <http://www.ymd.org>.

## TWR System Overview



Figure 2. Water movement through a TWR system. Note that not all TWR systems have the same components. Some TWR systems are comprised of only a large TWR ditch and no OFS reservoir.

**Tailwater recovery (TWR) systems** store water on the landscape to provide an alternative irrigation source for producers. Water used by irrigators from tailwater recovery systems directly offsets the amount of groundwater withdrawn from the aquifer. Thus, TWR systems are a popular conservation practice in the Mississippi Delta region. It is important to document how much water is saved and lost using TWR systems.

### TWR System Water Budget




Figure 3. Gains and losses of water into and out of TWR systems. Figure from Omer et al. (2017).

## TWR System Water Monitoring Results

### Water Budgets

Irrigators can use surface water from TWR systems as an alternative to groundwater. Data from eight locations in the Mississippi Delta region indicate that TWR systems 1) store surface water from October through May; 2) supply irrigators with water from June through July; and 3) lose considerable water to evaporation from August through September.

### TWR System Water Budget Results

Currently installed TWR systems have the capacity to offset aquifer depletion by 23,301 acre-feet a year by providing irrigators with an alternative to groundwater. Assuming each of the current TWR systems is installed on an individual farm, 2 percent of the farms in the Mississippi Delta region would reduce the groundwater deficit by 15 percent.




Figure 4. Mean (2013–16) quantity of water for each budget variable and water balance. From Omer et al. (2017).



Figure 5. TWR ditch in the Mississippi Delta region across four seasons.

## For More Information

Consult your county USDA Natural Resources Conservation Service agent for more details on conservation practices.

## References

- Omer, A. R., Dyer, J., Prince Czarnecki, J. M., Kröger, R., & Allen, P. J. (2017). Development of water budget for tailwater recovery systems in the Lower Mississippi Alluvial Valley. *Journal of Irrigation and Drainage Engineering* 144(6). [https://doi.org/10.1061/\(ASCE\)IR.1943-4774.0001302](https://doi.org/10.1061/(ASCE)IR.1943-4774.0001302)
- Barlow, J. R., & Clark, B. R. (2011). Simulation of water-use conservation scenarios for the Mississippi Delta using an existing regional groundwater flow model. Reston, VA: U.S. Department of the Interior, U.S. Geological Survey.
- YMD (Yazoo Mississippi Delta Joint Water Management District). (2010). Estimated 2010 groundwater use from the Mississippi River Valley Alluvial Aquifer. Stoneville, MS: YMD. Retrieved from <http://www.ymd.org/pdfs/YMD2010CropAnalysis.pdf>

---

Publication 3272 (POD-09-18)

By **Austin Omer**, PhD, former Extension Associate, and **Beth Baker**, PhD, Assistant Extension Professor, Wildlife, Fisheries, and Aquaculture.



**EXTENSION**

Copyright 2018 by Mississippi State University. All rights reserved. This publication may be copied and distributed without alteration for nonprofit educational purposes provided that credit is given to the Mississippi State University Extension Service.

Produced by Agricultural Communications.

Mississippi State University is an equal opportunity institution. Discrimination in university employment, programs, or activities based on race, color, ethnicity, sex, pregnancy, religion, national origin, disability, age, sexual orientation, genetic information, status as a U.S. veteran, or any other status protected by applicable law is prohibited. Questions about equal opportunity programs or compliance should be directed to the Office of Compliance and Integrity, 56 Morgan Avenue, P.O. 6044, Mississippi State, MS 39762, (662) 325-5839.

Extension Service of Mississippi State University, cooperating with U.S. Department of Agriculture. Published in furtherance of Acts of Congress, May 8 and June 30, 1914. GARY B. JACKSON, Director